



CE65H160DNGI

CoreGaN 650V GaN HEMT

Description

The CE65H160DNGI Series 650V, 160mΩ gallium nitride (GaN) FETs are normally-off devices.

Coreenergy GaN FETs offer better efficiency through lower gate charge, faster switching speeds, and lower dynamic on-resistance, delivering significant advantages over traditional silicon (Si) devices.

Coreenergy is a leading-edge wide band gap supplier with world-class innovation .

Application

- Adapter
- Renewable energy
- Telecom and data-com
- Servo motors
- Industrial
- Automotive

General Features

- Easy to drive—compatible with standard gate drivers
- Low conduction and switching losses
- RoHS compliant and Halogen-free

Benefits


- Increased efficiency through fast switching
- Increased power density
- Reduced system size and weight

Ordering Information


Part Number	Package	Package Configuration
CE65H160DNGI	DFN 8*8	Source



Top



Bottom



Circuit Symbol

Features

BV_{DSS}	$R_{DS(ON)}$	I_{DS}	Q_G
650V	160mΩ	14A	7.3nC



CE65H160DNGI

Absolute Maximum Ratings

$T_c=25^\circ\text{C}$ unless otherwise stated

Symbol	Parameter	Limit value	Unit
V_{DSS}	Drain to source voltage ($T_j = -55^\circ\text{C}$ to 150°C)	650	
$V_{(TR)DSS}$	Drain to source voltage-transient ^a	800	V
V_{GSS}	Gate to source voltage	-20~+20	
I_D	Continuous drain current @ $T_c=25^\circ\text{C}$ ^b	14	
	Continuous drain current @ $T_c=125^\circ\text{C}$ ^b	6	A
I_{DM}	Pulse drain current (pulse width: 10μs)	26	A
P_D	Maximum power dissipation @ $T_c=25^\circ\text{C}$	83	W
T_c	Operating temperature	Case	$-55\text{--}150$ $^\circ\text{C}$
T_j		Junction	$-55\text{--}150$ $^\circ\text{C}$
T_s	Storage temperature	-55~150	$^\circ\text{C}$

a. In off-state, spike duty cycle D<0.01, spike duration <1μs

b. For increased stability at high current operation



CE65H160DNGI

Thermal Resistance

Symbol	Parameter	Limit value	Unit
$R_{\theta JC}$	Junction-to-case	1.5	°C /W



Electrical Parameters

$T_J=25^\circ\text{C}$ unless otherwise stated

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
Forward Device Characteristics						
$V_{(\text{BL})\text{DSS}}$	Drain-source voltage	650	-	-	V	$V_{GS}=0\text{V}$
$V_{GS(\text{th})}$	Gate threshold voltage	1.2	1.7	2.2	V	
$\Delta V_{GS(\text{th})}/T_J$	Gate threshold voltage temperature coefficient	-	-7	-	mV/°C	$V_{DS}=1\text{V}, I_{DS}=1\text{mA}$
$R_{DS(\text{on})}$	Drain-source on-Resistance	-	160	210	mΩ	$V_{GS}=10\text{V}, I_D=1\text{A}, T_J=25^\circ\text{C}$
		-	340	-		$V_{GS}=10\text{V}, I_D=1\text{A}, T_J=150^\circ\text{C}$
I_{DSS}	Drain-to-source leakage current	-	1	10	μA	$V_{DS}=650\text{V}, V_{GS}=0\text{V}, T_J=25^\circ\text{C}$
		-	5	100		$V_{DS}=650\text{V}, V_{GS}=0\text{V}, T_J=150^\circ\text{C}$
I_{GSS}	Gate-to-source forward leakage current	-	-	±100	nA	$V_{GS}=\pm 20\text{V}$
C_{ISS}	Input capacitance	-	394	-		
C_{OSS}	Output capacitance	-	26	-	pF	$V_{GS}=0\text{V}, V_{DS}=400\text{V}, f=1\text{MHz}$
C_{RSS}	Reverse capacitance	-	0.93	-		
Q_G	Total gate charge	-	7.3	-		
Q_{GS}	Gate-source charge	-	1.2	-	nC	$V_{DS}=400\text{V}, V_{GS}=0\text{V to } 10\text{V}, I_D=1\text{A}$
Q_{GD}	Gate-drain charge	-	2	-		
Q_{OSS}	Output charge	-	37	-	nC	$V_{GS}=0\text{V}, V_{DS}=0\text{V to } 400\text{V}, f=1\text{MHz}$
$t_{D(\text{on})}$	Turn-on delay	-	2.5	-		
t_R	Rise time	-	7	-		
$t_{D(\text{off})}$	Turn-off delay	-	9.7	-	ns	$V_{DS}=400\text{V}, V_{GS}=0\text{V to } 10\text{V}, I_D=2.1\text{A}, R_{G-on(ext)}=6.8\Omega, R_{G-off(ext)}=2.2\Omega, L=250\mu\text{H}$
t_F	Fall time	-	28	-		



CE65H160DNGI

Electrical Parameters

$T_j=25^\circ\text{C}$ unless otherwise stated

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
Reverse Device Characteristics						
V_{SD}	Source-Drain reverse voltage	-	2.5	-	V	$V_{GS}=0\text{V}$, $I_{SD}=10\text{A}$
t_{RR}	Reverse recovery time	-	13	-	ns	
Q_{RR}	Reverse recovery charge	-	3.2	-	nC	$I_F=10\text{A}$, $V_{DD}=400\text{V}$, $dI_F/dt=165\text{A}/\mu\text{s}$

Typical Characteristics

$T_j=25^\circ\text{C}$ unless otherwise stated




Figure 1. Typical Output Characteristics $T_j=25^\circ\text{C}$




Figure 2. Typical Output Characteristics $T_j=125^\circ\text{C}$




Figure 3. Typical Transfer Characteristics ($V_{DS}=5\text{V}$)




Figure 4. Normalized On-resistance

Typical Characteristics

$T_j=25^\circ\text{C}$ unless otherwise stated




Figure 5. Typical Capacitance ($f=1\text{MHz}$)




Figure 6. Typical Gate Charge ($V_{DS}=400\text{V}$, $ID=1\text{A}$)




Figure 7. Typical C_{ooss} Stored Energy




Figure 8. Typical Q_{ooss}

Typical Characteristics

$T_j=25^\circ\text{C}$ unless otherwise stated




Figure 9. Channel Reverse Characteristics $T_j=25^\circ\text{C}$




Figure 10 Channel Reverse Characteristics $T_j=125^\circ\text{C}$




Figure 11. Transient Thermal Resistance




Figure 12. Power Dissipation

Typical Characteristics

$T_j=25^\circ\text{C}$ unless otherwise stated




Figure 13. Safe Operating Area $T_j=25^\circ\text{C}$




Figure 14. Switching times with inductive load

$V_{DS}=400\text{V}$, $V_{GS}=0\text{V}$ to 10V , $I_D=2.1\text{A}$,
 $R_{G-on(ext)}=6.8\Omega$, $R_{G-off(ext)}=2.2\Omega$, $L=250\mu\text{H}$





Figure 15. Switching times with waveform


PACKAGE DIMENSIONS

DFN8x8-8L-1.10-A


Top view



Bottom view



Side view(left/right)



Symbol	Min. (mm)	Mean. (mm)	Max. (mm)
A	1.05	1.10	1.15
A1	0	0.02	0.05
A2	0.203REF		
D	7.9	8	8.1
E	7.9	8	8.1
D1	0.9	1	1.1
D2	3.1	3.2	3.3
D3	2.7	2.8	2.9
E1	6.9	7	7.1
E2	0.4	0.5	0.6
E3	0.4	0.5	0.6
E4	6.9	7	7.1
e	1.9	2	2.1
b	0.9	1	1.1
L	0.4	0.5	0.6



CE65H160DNGI

Revision history

Major changes since the last revision

Revision	Date	Description of changes
1.0	2022-02-28	Initial release
2.0	2023-10-30	Mark change; Enrich dynamic specification curves
3.0	2023-12-25	Update dynamic parameters